

Searching by Document Number

** Result [Patent] ** Format(P805) 22.Aug.2003 1/ 1

Application no/date: 1990-286748[1990/10/24]
 Date of request for examination: [1993/05/31]
 Public disclosure no/date: 1992-163092[1992/06/08]
 Examined publication no/date (old law): []
 Registration no/date: []
 Examined publication date (present law): []
 PCT application no []
 PCT publication no/date []
 Applicant: TOPPAN PRINTING CO LTD
 Inventor: JOSA AKIO,NAITO AKIRA,YOSHIDA MASATO
 IPC: B41M 5/30
 FI: B41M 5/26 J
 F-term: 2H11AA01,AA27,AA33,AA47,BA03,BA08,BA09,BA37,BA39,BA53,BA55,BA61,BA63,BA78
 Expanded classification: 294,142
 Fixed keyword: R124
 Citation: [19,1995.10.27,03:04:11] (03,JP, Unexamined Publication of Patent,H02-196692) (03,JP, Unexamined Publication of Patent,H02-238995) (04,JP, Unexamined Publication of Patent,H02-196692) (04,JP, Unexamined Publication of Patent,H02-238995) (04,JP, Patent Application,H01-196774H@04JAA03-61087) (04,JP, Patent Application,H02-234739) (11,JP, Patent Application,H01-196774H@11JAJ03-61087) (11,JP, Patent Application,H02-234739H@11JAJ04-113889)
 Title of invention: THERMAL TRANSFER RECORDING MEDIUM
 Abstract:

PURPOSE: To form a sharp image without generating heat fusion with respect to a transfer material having no release agent added thereto at the time of transfer by adding silicone modified polymer to the ink layer of a thermal transfer recording medium in a specific ratio.

CONSTITUTION: A thermal transfer recording medium is formed by providing an ink layer 1 to a base material 2 and providing a heat-resistant lubricating layer 3 to the surface on the side opposite to the ink layer 1 of the base material 1. The ink layer 1 contains a thermal transfer dye, a binder and 0.1-10wt.% of a silicone modified polymer. The silicone modified polymer has the same release effect as silicone and has the compatibility with the binder of the ink layer. Therefore, the heat fusion of the thermal transfer recording medium and a transfer

COPYRIGHT: (C) 1992, JPO&Japio